



1/2" DEEP IMPACT SOCKET SET AF DIN FOAM1 14 PIECES

- DIN standard design for use with a retaining pin and ring
- Chrome molybdenum for use with power tools
- Black phosphate finish for easy identification as an impact socket
- Ring and pin fixing hole on the female end to secure the socket
- Retaining ring and pin included in the set
- Tools are held in place using three colour pre-cut high-density EVA foam clearly showing where each tool belongs
- Designed and manufactured to ASME B107110
- Organised in a foam inlay module size 1 (FOAM1)

Impact Socket Set 1/2" Drive AF Deep 14 pieces

General information

Country of origin: Taiwan
Barcode: 5020385020474
Tariff code Europe: 8204200000
ECCN US: EAR99
UNSPSC: 27111703

Dimensions

Net weight (g): 2317
Width (mm): 142
Depth (mm): 265
Height (mm): 50

Attributes

Product type: Impact Tool Sets
Certificates: N/A
Number of pieces: 14
Drive: 1/2"
Socket type: Deep, 6-point
Standard type: DIN
Unit of measurement: AF
Inlay material: FOAM
Type of set: FOAM1

Features



Technical changes and errors may occur. 01-08-2024 19:59



DESIGNED IN SWEDEN

TengTools is a Swedish company present in more than 30 markets worldwide, and offers hand tools in smart storage solutions for demanding professionals within the automotive, maintenance and engineering sectors, as well as motor sport enthusiasts who aspire to use the same tools as top mechanics across the globe.



Sandbergsvägen 3
 441 39 Alingsås, Sweden

ADDITIONAL IMAGES



WWW.TENGOOLS.COM



TENGOOLS TEA9214LAF



LIST OF CONTENTS



TEA9214LAF	1/2" Deep Impact Socket Set AF DIN FOAM1 14 Pieces
920214	1/2" Deep Impact Socket DIN AF 7/16"
920216	1/2" Deep Impact Socket DIN AF 1/2"
920218	1/2" Deep Impact Socket DIN AF 9/16"
920220	1/2" Deep Impact Socket DIN AF 5/8"
920222	1/2" Deep Impact Socket DIN AF 11/16"
920224	1/2" Deep Impact Socket DIN AF 3/4"
920226	1/2" Deep Impact Socket DIN AF 13/16"
920228	1/2" Deep Impact Socket DIN AF 7/8"
920230	1/2" Deep Impact Socket DIN AF 15/16"
920232	1/2" Deep Impact Socket DIN AF 1"
O92194	Retaining Ring 19 × 4.0 mm
O92244	Retaining Ring 24 × 4.0 mm
P92320	Retaining Pin 3 × 20 mm
P92325	Retaining Pin 3 × 25 mm