



STUBBY RATCHETING COMBINATION SPANNER SET TT1 10 PIECES

- Short stubby spanners for use in confined spaces.
- 72 teeth ratchet spanners giving a 5° increment between clicks.
- Hip Grip on the ring end, turn spanner over to change direction.
- Chrome vanadium satin finish
- Organised in a tool tray module size 1 (TT1)

Metric Stubby Ratcheting Combination Spanner Set 10 piece

General information

Country of origin: Taiwan
Barcode: 5020385044777
Tariff code Europe: 8204110000
ECCN US: EAR99
ETIM: EC002209
UNSPSC: 27111713

Dimensions

Net weight (g): 1137
Width (mm): 142
Depth (mm): 265
Height (mm): 50

Attributes

Product type: Spanners & Wrench Sets
Certificates: N/A
Number of pieces: 10
Spanner type: Stubby
Ratcheting: Yes
Unit of measurement: Metric
Inlay material: PS
Type of set: TT1

Features



Technical changes and errors may occur. 01-08-2024 19:52



DESIGNED IN SWEDEN

TengTools is a Swedish company present in more than 30 markets worldwide, and offers hand tools in smart storage solutions for demanding professionals within the automotive, maintenance and engineering sectors, as well as motor sport enthusiasts who aspire to use the same tools as top mechanics across the globe.



Sandbergsvägen 3
 441 39 Alingsås, Sweden

ADDITIONAL IMAGES



WWW.TENGOOLS.COM



LIST OF CONTENTS



TT6010MRS Stubby Ratcheting Combination Spanner Set TT1 10 Pieces

- 6005M10RS** Stubby Ratcheting Combination Spanner Metric RS 10 mm
- 6005M11RS** Stubby Ratcheting Combination Spanner Metric RS 11 mm
- 6005M12RS** Stubby Ratcheting Combination Spanner Metric RS 12 mm
- 6005M13RS** Stubby Ratcheting Combination Spanner Metric RS 13 mm
- 6005M14RS** Stubby Ratcheting Combination Spanner Metric RS 14 mm
- 6005M15RS** Stubby Ratcheting Combination Spanner Metric RS 15 mm
- 6005M16RS** Stubby Ratcheting Combination Spanner Metric RS 16 mm
- 6005M17RS** Stubby Ratcheting Combination Spanner Metric RS 17 mm
- 6005M18RS** Stubby Ratcheting Combination Spanner Metric RS 18 mm
- 6005M19RS** Stubby Ratcheting Combination Spanner Metric RS 19 mm